

MIRROR DE-MISTING PANEL INSTALLATION MANUAL

NO MORE MISTY MIRRORS!

Mirror de-misting panel is the totally safe and simple answer to steamed-up mirrors. It is double insulated and designed for use in wet areas such as bathrooms, shower rooms, etc. The panel is only 0.4mm thick. It is simply installed by peeling off the self-adhesive backing and sticking it directly onto the back of the mirror. The capacity of each panel is sufficient to warm up the mirror to 30 °C in 3 to 5 minutes. The surface temperature of the mirror is limited to 45°C. To save energy, the panel wires are connected to the lighting system and switched on only when required. The mirror de-misting panel is for de-misting the mirror and is not a bathroom heater.

Note: The mirror should not be cut, drilled or altered in any way as this may weaken the mirror.

INSTALLATION:

Mirror de-misting panels designed for glass mirrors only. Ensure the mirror is larger than the mirror de-misting panel. Carefully peel off self-adhesive backing from the mirror de-misting panels and place directly onto the back of the mirror making sure there are no creases or bubbles. Allow for heat expansion when mounting the mirror i.e. do not butt tiles hard against the mirror allow a silicone expansion gap.

- Do not fit mirror onto or near metallic surfaces, i.e. Aluminium, Stainless steel etc.
- Corner brackets must have clearance to allow for expansion.
- If fitting mirror to wall using adhesive, the adhesive should be placed around the edge of the mirror (Minimum 40 mm gap between panel and edge of mirror).
- Do not put adhesive onto the mirror de-misting panel.
- Do not cut, drill or weaken the mirror structure in any way.
- Do not cut or alter the mirror de-misting panel.
- Wiring should be carried out in accordance with IEE regulations.

NOTE: All electrical connections should be undertaken by a qualified electrician. An MCB or RCCB must be used as applicable.

TECHNICAL DATA:

Size	: 40 x 58 cm (50Watt)
Voltage	: 230 V
Capacity	: 65 watts
Thickness	: 0.4mm
Cable length	: 100 cm
Standard	: IP34 Class 2
Approval	: FIMKO, European Standard CE
Temperatures	: Ca 40 to 50 °C Maximum